

Features

- The AN-100CM powers up to ten microphones
- Conference microphones daisy chain with standard XLR cables
- Cardioid electret microphones have excellent "pick-up"
- Each microphone has adjustable volume control
- 16 Channel UHF Wireless mic option for audience Q&A
- Chairman microphone can mute all delegate microphones
- Immunity from mobile telephone interference
- 1/4" & XLR balanced Line Out for recording, connection to house audio system or Assistive Listening System
- 3.5mm Line In for music player device
- Reaches crowds up to 100 people

Anchor Audio's portable conference system travels from the council chambers to community center with ease of setup and simplicity of use. The CouncilMAN is flexible to the demands of most room sizes and manages up to ten microphones. With an optional wireless microphone the panel takes questions from the audience.

Technical Specifications

AN-100CM Console Speaker

Rated Power Output	30 watts
Max SPL @ Rated Power	106 dB @ 1 meter
Frequency Response	65 Hz - 18 kHz $\pm$ 3 dB
Speaker Type	4.5" woofer, 10 mm dome tweeter
	Magnetically Shielded
AC Power Reqs.	100 - 240 VAC, 50/60 Hz
Fuse Rating	T 1.0A / 250V (internally mounted)
Export Model	T 0.5A / 250V (internally mounted)

CHM-100/DEL-100 Microphone Base

Power Requirement	+22 VDC @ 60 mA from pin 2 of daisy chain
Output Impedance	>10k ohms
Phantom Power	18V
Dimensions (HWD)	5.8 x 6.5 x 1.75" / 14.73 x 16.51 x 4.45 cm
Weight	0.90 lbs / .41 Kg
Daisy Chain In/Out	Male and Female 3 pin XLR
CHM-100 Controls	Push to Talk, Volume and Mute Others
DEL-100 Controls	Push to Talk and Volume
Warranty	2 years

Line In	3.5mm
Line Out	Lo-Z, buffered, XLR and 1/4" Balanced
Line Output Level	-20 dBV (100 mVrms)
Enclosure Material	ABS Plastic
Dimensions (HWD)	5.25 x 8.4 x 9" / 13 x 21 x 23 cm
Weight	8.5 lbs / 3.8 Kg
Warranty	6 years

LM-618 Gooseneck Microphone

Pickup Pattern	Cardioid
Type	Back Electret Condenser
Phantom Power	9 - 52 Volts DC
Impedance	200 Ohms @ 1kHz
Response	80 Hz - 17 kHz $\pm$ 3dB
Sensitivity	-56 dB @ 1 kHz open circuit (0 dB = 1 V/ μ bar)
Dimension	18.75" from mic tip to XLR top, 2 flex sections
Microphone	0.54" O.D.
Warranty	2 years



PACKAGES

CM-4 includes one chairman mic, three delegate mics, one AN-100CM speaker/amplifier, three 4' XLR cables and one 25' XLR cable in a sturdy carrying case with foam inserts.

CM-4W includes one chairman mic, three delegate mics, one AN-100CMU1 speaker/amplifier with built-in UHF receiver, one handheld mic, three 4' XLR cables and one 25' XLR cable in a sturdy carrying case with foam inserts.

CM-6 includes one chairman mic, five delegate mics, one AN-100CM speaker/amplifier, five 4' XLR cables and one 25' XLR cable in a sturdy carrying case with foam inserts.

CM-6W includes one chairman mic, five delegate mics, one AN-100CMU1 speaker/amplifier with built-in UHF receiver, one handheld mic, five 4' XLR cables and one 25' XLR cable in a sturdy carrying case with foam inserts.

ANCHOR AUDIO, INC.
PORTABLE SOUND SYSTEMS

TORRANCE, CALIFORNIA
www.anchoraudio.com

800.262.4671

