

TECHNICAL SPECIFICATIONS

| | |
|-------------------------------|---|
| Rated Power Output | 200 Watts thru RMS |
| Max SPL @ Rated Power | 123 dB @ 1 meter |
| Frequency Response | 40 Hz – 20 kHz ± 3dB |
| AC Power Input | 100 – 240 V~AC, 50-60 Hz, 3A |
| USB (Charging Only) | 5V / 2.5 Watts |
| Battery | Two 12.8 V rechargeable, 10.2 Ah (LiFePO4 Lithium Iron Phosphate Battery) Full recharge: approx. 5 hrs. |
| Flex Radio | 1.9 GHz DECT 6.0 or EU-DECT ≈ 300' line of sight Frequency Response 20Hz - 20kHz ± 3dB |
| Bluetooth | 2.5 GHz ≈ 60' line of sight Frequency Response 20Hz - 20kHz ± 3dB |
| Microphone Inputs | Lo-Z, balanced, XLR 36VDC condenser mic (phantom) power |
| Microphone Wireless Frequency | 1.9 GHz DECT 6.0 or EU-DECT ≈ 300' line of sight Frequency Response 20Hz - 11.30KHz ± 3dB |
| Line Inputs | Unbalanced 3.5mm stereo & Balanced 1/4" |
| Line Output | PreFader, isolated, 600Ω, 1/4" phone |
| Dimensions (HWD) | With Back Cover: ≈ 22.00" x 15.50" x 14.50" [56 x 40 x 37cm] Without Back Cover: ≈ 22.00" x 15.50" x 12.75" [56 x 40 x 33cm] |
| Weight | ≈ 44 lbs / 20 Kg |
| Speakers | One, 10" Woofer, Ceramic Magnet, 4 ohms One, 1.33" compression driver, Ceramic Magnet, 8 ohms |
| Compliance | BT FCC ID: 2AMWO-FSCBT1026 / IC ID: 23872-FSCBT1026 WAM DECT Radio FCC ID: Y82-SC145 / IC ID: 9576A-SC145 RoHS3 |



ENVIRONMENTAL SPECIFICATIONS

- Maximum operating temperature up to 40°C
- Maximum operating altitude up to 2000 m
- Pollution degree 2
- Must use fuses rated F2AH 250V
- Disconnect the power before servicing

(All specifications are subject to change without notice.)