

LIBERTY 3

TECHNICAL SPECIFICATIONS

| | |
|---------------------------------|--|
| Rated Power Output | 200 watts |
| Max SPL @ Rated Power | 123 dB @ 1 meter |
| Frequency Response | 40 Hz ~ 20 kHz \pm 3dB |
| AC Power Reqs | 100~240 VAC, 50/60 Hz, 2A |
| Charger/Power Inlet | PC-2 |
| Battery | Two 12.8V Lithium Iron Phosphate rechargeable (LiFePo4), 10.2 Ah Full recharge: ~ 5 hours |
| AnchorLink 3 Wireless Frequency | 1920~1930 MHz USA/CAN; 1880~1900 MHz Europe |
| AnchorLink 3 Wireless Range | 300' + line of sight |
| AnchorFlex Frequency Range | 1920~1930 MHz USA/CAN; 1880~1900 MHz Europe |
| AnchorFlex Wireless Range | 300' + line of sight |
| Microphone Inputs | <ul style="list-style-type: none">Lo-Z (1 kW), balanced, XLR & 1/4"36 V DC condenser mic (phantom) powerHi-Z (10 kΩ), unbalanced, 1/4" phone |
| Line Inputs | Balanced 1/4" & Unbalanced 3.5 mm stereo |
| Line Output (post fader) | Isolated, 600 Ω , 1/4" phone |
| Dimensions (HWD) | With Back Cover: 22.00" x 14.00" x 14.5" (56 x 40 x 37 cm) Without Back Cover: 22.00" x 15.50" x 12.75" (56 x 40 x 33 cm) |
| Weight | 44 lbs / 20 Kg |



ENVIRONMENTAL SPECIFICATIONS

- Maximum operating temperature up to 40°C
- Maximum operating altitude up to 2000 m
- Pollution degree 2
- European market must use fuses rated F2AH 250V, Fast Blow shall be installed on both LINE and NEUTRAL of AC mains input.
- Disconnect the power before servicing.

(All specifications are subject to change without notice.)